



AERONS (INDIA)

dB Series

Premium Amplifier Series

CLASS H STAGE III



	dB 7000	dB 8000	dB 9000	dB 11000
8Ω Stereo Power	1300W	1500W	1900W	2100W
4Ω Stereo Power	2300W	2600W	3000W	3600W
2Ω Stereo Power	3500W	4000W	4500W	5400W
8Ω Bridge Power	4600W	5200W	6000W	7200W
4Ω Bridge Power	7000W	8000W	9000W	10800W
Output Circuitry	CLASS H			
Frequency response (1W@8Ω)	20Hz-20kHz +1/-1Db			
THD+N (20Hz-20kHz for 1W THD+N)	<0.1%			
Damping factor	800	800	1300	1300
S/N rate	≥100dB			
Input Sensitivity	0.775V/1.2V/2.5V			
Input impedance	>10KΩ, Balance or Unbalanced, All Models			
Input Connector	Male XLR, Female XLR			
Output Connector	2x NL4 SpeakON			
Rear Panel Control	Input Mode Switch: Stereo/ Parallel/ Bridge, Sensitivity: 0.775V/1.4V/2.5V, Limiter: OFF/ON, Grounding: Lift/Ground			
Dimensions	483x132x577.3mm			
Power Requirement	220V/50-60Hz			
Net Weight	38.5kgs	39kgs	39.5kgs	40kgs